



EV ZLX 12 Passive Speaker

Ideal for main loudspeaker or monitor wedge duties, the ZLX-12 offers the ultimate combination of performance and portability – and always looks great on stage.



Physical

Size of Unit	356 x 610 x 356mm
Item weight	14.9kg
Size of unit cased	822 x 822 x 422mm
Cased weight	65kg (Pair)
Quantity in case	2
LF Driver	12"
HF Driver	1.5" Compression Driver
Enclosure Construction	Polypropylene

Electrical

Rated Power	N/A
Input Power	N/A
Power Connection	N/A

Mounting Options

Speaker Stand	Yes
Horizontal / Vertical	-
Foldback Wedge	Yes
Flyware Options	No

Inputs / Outputs

Type	NL4 (pins 1+/-)
Numbers	2

Parameters

Passive / Active	Passive
Horn Dispersion / Rotatable	90° wide x 60° vertical / No
Frequency Response	82 Hz – 18 kHz
Max SPL (1m, Full Space)	125 dB
Sensitivity	95 dB
Power Handling (RMS)	250w
Power Handling	1000w
Crossover Frequencies	LF<>HF @2.1KHz
Nominal Impedance	8 Ohms

Environmental

IP Rating	N/A
Cooling	Ports
Max Operating Temperature	N/A

Accessories Included

Speaker bag for single speaker deployment

Compatibility

	QSC GX5 Amp 2 Channels NL4 OUT	Nexo P58 Amp 2 Channels NL4 OUT	Nexo NX Amp 4x1000w 4 Channels NL4 OUT	Nexo NX Amp 4x4000w 4 Channels NL4 OUT	Camco Vortex 4 Amp (4000w) 2 Channels NL4 OUT	Camco Vortex 6 Amp (6000w) 2 Channels NL4 OUT	Camco D3 Amp (3200w) 2 Channels NL4 OUT	D&B D12 Amp 2 Channels EPS OUT	D&B D20 Amp 4 Channels NL4 OUT
Speaker EV ZLX 12 Passive NL4	2 per channel PREFERRED	X	3 per channel	3 per channel	3 per channel	3 per channel	3 per channel	3 per channel	2 per channel

Information Links

Manufacturer Link [EV ZLX](#)

Manufacturer Manual [EV ZLX MANUAL](#)