



RCF 422ART (12" Active)

The ART 422-A is a two-way active speaker delivering an extremely linear frequency response and precise, deep low frequency control thanks to the perfect blend of the fast and high efficiency transducers. A transparent midrange sound and extremely fidelity in high frequencies are guaranteed by the new 2" neodymium compression driver specially developed for this speaker.



Physical

Size of Unit	637 x 384 x 363mm
Item weight	20.2kg
Size of unit cased	N/A
Cased weight	N/A
Quantity in Case	1
LF Driver	12" High Power Neodymium Woofer, 3" Voice Coil
HF Driver	2" Titanium Dome, Neodymium High Frequency Driver
Enclosure Construction	Polypropylene Composite

Electrical

Rated Power	400w
Input Power	240v
Power Connection	IEC

Mounting Options

Speaker Stand	Yes
Horizontal / Vertical	Yes
Foldback Wedge	Yes

Inputs / Outputs

Input Type	XLR (1), 6.5mm Jack (1)
Numbers	2
Output Type	6.5mm Jack (1)
Number	1

Parameters

Passive / Active	Active
Horn Dispersion / Rotatable	No
Frequency Response	50 Hz – 20 kHz
Max SPL	127 dB
Sensitivity	+4dBu
Power Handling (RMS)	400w
Power Handling (Peak 10ms)	800w
Crossover Frequencies	1800 Hz
Nominal Impedance	N/A

Environmental

IP Rating	No
Cooling	Convection
Max Operating Temperature	-

Accessories Included

Speaker Bag

Information Links

Manufacturer Link [RCF 422ART](#)

Data Sheet [Spec Sheet](#)

Data Sheet [Rigging Guide](#)