



RCF 702-AS Sub

Housing a 12" woofer, the SUB 702-AS is a very compact active sub enclosure and features a 1400 W powerful digital amplifier. It is the ideal complement to 8" or 10" speakers, creating small but powerful satellite systems with outstanding performance. Thanks to its compact size it can easily be carried and is very quick and easy to start using the built-in digital stereo crossover (DSP) with adjustable crossover frequency to connect the satellite.



Physical

Size of Unit	487 x 354 x 498mm
Item weight	19kg
Size of unit cased	620 x 480 x 780mm
Cased weight	46kg
LF Driver	12" Woofer, 2.5" Voice Coil
HF Driver	N/A
Enclosure Construction	Baltic Birch Ply

Electrical

Rated Power	700w
Input Power	240v
Power Connection	IEC

Mounting Options

Speaker Stand	No
Horizontal / Vertical	-
Foldback Wedge	N/A

Inputs / Outputs

Input Type	XLR
Numbers	L/R Pair
Output Type	XLR through / Xover out
Number	L/R Pair

Parameters

Passive / Active	Active
Horn Dispersion / Rotatable	N/A
Frequency Response	40 Hz – 120 kHz
Max SPL	129 dB
Sensitivity	+4dBU
Power Handling (RMS)	700w
Power Handling (Peak 10ms)	1400w
Crossover Frequencies	LPF / HPF Xover Out @ 80/110 Hz
Nominal Impedance	N/A

Environmental

IP Rating	No
Cooling	Convection
Max Operating Temperature	-

Information Links

Manufacturer Link [RCF 702-AS 12" Sub](#)

Data Sheet [User Guide](#)